

HONDA EB10000

- COMPATIBLE WITH THE LIGHTWEIGHT DLX ASAP® LINE.

ONE-PERSON TRANSPORTABLE.

At Deployed
Logix we're
redefining rapid

deployment. Through

deployment. Through

our extensive work with law

enforcement, search and rescue

teams, various first responders, private

organizations both domestically and abroad,

and the military, our team understands that when

a crisis calls, seconds count. Discover why we are

the leader in American-made, rapidly deployable disaster

preparedness products.

Specification and design may be altered without notice due to continuous product development. LAST UPDATED NOVEMBER 2022.

Proudly made in the USA.

CAGE CODE: 7CFK2 | DUNS#: 079751064

- POWER FOR MULTIPLE HVAC UNITS.
 - THE PERFECT BALANCE OF POWER AND LOGISTICS.



HONDA EB10000 SPECIFICATIONS				
DIMENSIONS (L X W X H):	55.90 x 26.70 x 35.10 in (141.99 x 67.82 x 89.15 cm)			
DRY WEIGHT:	403 lb (182.8 kg)			
ENGINE:	Honda GX630			
DISPLACEMENT:	630cc			
AC OUTPUT:	 120/240V 10000 W max (83.8/41.6 A) 9000 W rated (75/37.5 A) 			
DC OUTPUT:	N/A			
IAVR OUTPUT:	N/A			
STARTING SYSTEM:	Electric			
FUEL TANK CAPACITY:	8.1 gal. (30.6 L)			
RUN TIME PER TANKFUL:	4.6 hr @ rated load, 7.2 hr @ 50% load			
NOISE LEVEL:	73 dBA @ rated load, 71 dBA @ 50% load			
SERVICE CONNECTIONS:	120V AC 20 A	120V AC 30 A	120/240V AC 30 A	120/240V AC 37.50 A
PLUG TYPE:	(4) NEMA 5-20R	(1) NEMA L5-30R	(1) NEMA L14-30R	(1) CS-6369



