

HONDA EU3000

· INVERTER - STABLE POWER FOR COMPUTERS AND MORE.

- THE PERFECT BALANCE OF POWER AND LOGISTICS.
 - CONVENIENT ELECTRIC START.
 - SUPER QUIET.

deployment. Through
our extensive work with law
enforcement, search and rescue
teams, various first responders, private
organizations both domestically and abroad,
and the military, our team understands that when
a crisis calls, seconds count. Discover why we are
the leader in American-made, rapidly deployable disaster
preparedness products.

At Deployed Logix we're

Specification and design may be altered without notice due to continuous product development. LAST UPDATED NOVEMBER 2022.

Proudly made in the USA.
CAGE CODE: 7CFK2 | DUNS#: 079751064



HONDA EU3000 SPECIFICATIONS		
DIMENSIONS (L X W X H):	25.90 x 17.60 x 22 in (65.79 x 44.70 x 55.88 cm)	
DRY WEIGHT:	131 lb (59.4 kg)	
ENGINE:	Honda GX200	
DISPLACEMENT:	196 cc	
AC OUTPUT:	120V 3000 W max. (25 A) 2800 W Rated (23.3 A)	
DC OUTPUT:	12V, 144 W, 12 A	
STARTING SYSTEM:	Recoil, electric	
FUEL TANK CAPACITY:	3.4 gal. (12.8 L)	
RUN TIME PER TANKFUL:	7.1 hr @ rated load, 20 hr @ 25% load	
NOISE LEVEL:	57 dBA @ rated load, 50 dBA @ 25% load	
SERVICE CONNECTIONS:	120V AC 20A	120V AC 30A
PLUG TYPE:	(2) NEMA 5-20R GFCI	(1) NEMA L5-30R