

HONDA EU7000

THE PERFECT BALANCE OF POWER AND LOGISTICS.

INVERTER - STABLE POWER FOR COMPUTERS AND MORE.

CONVENIENT ELECTRIC START.

SUPER QUIET.

Logix we're redefining rapid deployment. Through our extensive work with law enforcement, search and rescue teams, various first responders, private

At Deployed

organizations both domestically and abroad, and the military, our team understands that when a crisis calls, seconds count. Discover why we are the leader in American-made, rapidly deployable disaster preparedness products.

Specification and design may be altered without notice due to continuous product development. LAST UPDATED NOVEMBER 2022.

> Proudly made in the USA. CAGE CODE: 7CFK2 | DUNS#: 079751064



HONDA EU7000 SPECIFICATIONS			
DIMENSIONS (L X W X H):	33.40 x 27.60 x 28.40 in (84.84 x 70.10 x 72.14 cm)		
DRY WEIGHT:	260.4 lb (118.1 kg)		
ENGINE:	Honda GX390 EFI		
DISPLACEMENT:	389 cc		
AC OUTPUT:	120 / 240V, 7000 W max.(58.3/29.1 A) 5500 W rated (45.8/22.9 A)		
DC OUTPUT:	NA		
STARTING SYSTEM:	Recoil, electric		
FUEL TANK CAPACITY:	5.1 gal. (20.4 L)		
RUN TIME PER TANKFUL:	6.5 hr @ rated load, 18 hr @ 25% load		
NOISE LEVEL:	58 dBA @ rated load, 52 dBA @ 25% load		
SERVICE CONNECTIONS:	120V AC 20A	120V AC 30A	120/240V AC 30A
PLUG TYPE:	(4) NEMA 5-20R GFCI	(1) NEMA L5-30R	(1) NEMA L14-30R



