



TAKE IT UP A NOTCH.  
**SHELTER OPTIONS**

# RIGID DOOR

- **INTERCHANGEABLE BETWEEN ASAP® AND X-SERIES SHELTERS.**
- **WORKS WITH CURRENT AND PAST SHELTER SYSTEMS.**
- **IMPROVES EASE OF ACCESSIBILITY.**
- **DIMENSIONS (W X H): 53 X 86 IN (134.62 X 218.44 CM).**

At Deployed Logix we're redefining rapid deployment. Through our extensive work with law enforcement, search and rescue teams, various first responders, private organizations both domestically and abroad, and the military, our team understands that when a crisis calls, seconds count. Discover why we are the leader in American-made, rapidly deployable disaster preparedness products.

Specification and design may be altered without notice due to continuous product development. LAST UPDATED AUGUST 2022.

Proudly made in the USA.  
CAGE CODE: 7CFK2 | DUNS#: 079751064



RIGID DOOR SPECIFICATIONS	
PACKING METHOD (L X W X H):	DLX Labeled Zipper Bag, 82 x 22 x 4 in (208.28 x 55.88 x 10.16 cm)
PACKED DIMENSIONS (L X W X H):	82 x 22 x 4 in (208.28 x 55.88 x 10.16 cm)
DIMENSIONS (W X H):	85.50 x 54 in (217.17 x 137.16 cm)
SWING RADIUS:	36 in (91.44 cm)
RAMP DIMENSIONS (L X W X H):	48.50 x 16.50 x 2 in (123.19 x 41.91 x 5.08 cm)
TOTAL WEIGHT:	63 lb (28.57 kg)
MATERIALS:	
<b>Door Frame:</b> Powder coated extruded aluminum rectangular tube	
<b>Soft Components:</b> 12.5 oz/yd <sup>2</sup> Vinyl, Laminated, Polyester, Woven Class 1 Camouflage Green 483 or Class 2 Desert Tan 459, Grade A MIL-PRF-44103D USIFI-PRF-44103A	
<b>Foot Plate:</b> Texture powder coated aluminum	
ATTACHMENT METHOD:	
<b>Frame Attachment:</b> Upper brace bar wedge with hook & loop, secured with thumb screws	
<b>Soft Cover Attachment:</b> Hook & loop	
<b>Install Position:</b> Exterior doorway	
SHELTER COMPATIBILITY:	All *ASAP® & *X-Series Shelters
KIT INCLUDES:	(1) Rigid Door Folding Frame (1) Foot Plate Ramp (2) Upper Brace Arms (1) Door Frame Soft Connector (1) Soft Door Panel (1) Door Awning for ASAP® (4) Thumb Screws for Upper Brace Arms



*\*ASAP® Installation*



*\*X-Series Installation*