



JUST THE WAY YOU LIKE IT.
CLIMATE CONTROL

XW-70 HEATER, 120V

- **TRI-FUEL CAPABILITIES: DIESEL, KEROSENE, AND JP8.**
- **QUICK OPERATING AND EASY-TO-CONTROL SYSTEM EVEN IN EXTREME WEATHER CONDITIONS.**
- **HEATS MULTIPLE SHELTERS AT ONCE.**
- **CONVENIENTLY PACKED IN A SINGLE 75-INCH BEST CASE BY DLX™.**

At Deployed Logix we're redefining rapid deployment. Through our extensive work with law enforcement, search and rescue teams, various first responders, private organizations both domestically and abroad, and the military, our team understands that when a crisis calls, seconds count. Discover why we are the leader in American-made, rapidly deployable disaster preparedness products.

Specification and design may be altered without notice due to continuous product development. LAST UPDATED NOVEMBER 2022.

Proudly made in the USA.
CAGE CODE: 7CFK2 | DUNS#: 079751064



XW-70 HEATER, 120V SPECIFICATIONS	
DEPLOYED DIMENSIONS (L X W X H):	44.50 x 19 x 24 in (113.03 x 48.26 x 60.96 cm)
PACKED DIMENSIONS (L X W X H):	75.63 x 25 x 24 in (192.10 x 63.50 x 60.96 cm)
HEATING CAPACITY:	70000 BTU/hr, 20.5 kW
RATED AIRFLOW:	910 CFM, 1546 m ³ /hr
FUEL TYPES:	DF1, DF2, DFA, JP8
FUEL TANK:	11.6 gal. (43.9 L)
FUEL CONSUMPTION:	0.55 gal./hr (2 L/hr)
RUN TIME:	21 hr/tank
POWER:	120V // 1 PH // 60 Hz
RUNNING LOAD AMPS:	3 A
RUNNING LOAD WATTS:	360 W
PLUG TYPE:	15 A standard plug
DUCT ADAPTER-SUPPLY:	12 in (30.48 cm)
DUCT ADAPTER-RETURN:	12 in (30.48 cm)
PACKING METHOD:	(1) Best Case By DLX™
DEPLOYED WEIGHT:	84 lb (38.1 kg)
FEATURES:	<ul style="list-style-type: none"> • Stainless steel burn chamber • Auto safety control devices • Electronic flame control • Powder-coated cabinet • UL listed U.S. / Canada