



**FIELD ASSETS**  
ADDITIONAL SUPPORT WHEN YOU NEED IT.

# ACTIVE PATIENT CARE BED

- **VERSATILE MEDICAL BED DEPLOYS IN TWO MINUTES.**
- **28-INCH TALL BED PRESENTS PATIENTS AT COMFORTABLE WORKING HEIGHT.**
- **WATER-RESISTANT, ANTI-MICROBIAL, SOIL-RESISTANT MATTRESS.**
- **450 LB (204.1 KG) WORKING CAPACITY.**

At Deployed Logix we're redefining rapid deployment. Through our extensive work with law enforcement, search and rescue teams, various first responders, private organizations both domestically and abroad, and the military, our team understands that when a crisis calls, seconds count. Discover why we are the leader in American-made, rapidly deployable disaster preparedness products.

Specification and design may be altered without notice due to continuous product development. LAST UPDATED JULY 2022.

Proudly made in the USA.  
CAGE CODE: 7CFK2 | DUNS#: 079751064



ACTIVE PATIENT CARE BED SPECIFICATIONS					
DEPLOYED DIMENSIONS:	80 x 32 x 28 in (203.20 x 81.28 x 71.12 cm)				
STORED DIMENSIONS:	42 x 32 x 8 in (106.68 x 81.28 x 20.32 cm)				
SLEEPING SURFACE:	80 x 32 in (203.20 x 81.28 cm)				
BED PERSONNEL CAPACITIES:	3 Beds	4 Beds	6 Beds	8 Beds	10 Beds
	ASAP-12	ASAP-18 ASAP-HUB X-HUB	X-24 / X-24SC	X-32	X-40 / X-40SC
CURB WEIGHT:	30 lb (13.6 kg)				
WORKING CAPACITY:	450 lb (204.1 kg)				
FRAME MATERIAL:	Lightweight, rust-resistant, aluminum frame				
MATTRESS MATERIAL:	Antimicrobial, soil-resistant, triple-layer vinyl				
CFR 1633 COMPLIANT:	YES				
ADA COMPLIANT:	YES				
SAFETY FEATURES:	<ul style="list-style-type: none"> <li>Exceeds settle load testing at 15K cycles x 450 lb (204.1 kg)</li> <li>Friction welded (spun) tubular ends</li> <li>Heavy-duty leg locks</li> <li>Reinforced vinyl-coated decking</li> <li>Wide patient restraint belt</li> <li>Antimicrobial, soil-resistant decking material</li> <li>Easy to decontaminate</li> <li>Safety and instructional labeling</li> </ul>				
COMFORT FEATURES:	<ul style="list-style-type: none"> <li>5-position head elevator with locking cord</li> <li>2-position Trendelenburg foot elevator</li> <li>2 in (5.08 cm) convoluted foam mattress</li> <li>Customizable sleeping surface</li> <li>Wheelchair transferrable height</li> <li>Spring and deck design</li> <li>Combined spring stretch resistance of 5472 lb (2482.1 kg)</li> </ul>				
CONVENIENCE:	<ul style="list-style-type: none"> <li>Stores securely in EMS vehicles and in small compartments</li> <li>Optional stow-on-board safety rails</li> <li>Optional stow-on-board IV pole</li> </ul>				
APPLICATION:	Ems vehicle rapid response, surge capacity, special needs, mass care, functional needs care, & medical				
WARRANTY:	Standard One Year Warranty				