



JUST THE WAY YOU LIKE IT.  
**CLIMATE CONTROL**

# 5.0 TON HVAC

- **ALL-IN-ONE CLIMATE CONTROL SOLUTION.**
- **CAPABLE OF 62,000 BTU/HR COOLING AND 60,000 BTU/HR HEATING.**
- **SELF-CONTAINED AND PORTABLE.**
- **OUTDOOR, ALL-WEATHER UNIT.**

At Deployed Logix we're redefining rapid deployment. Through our extensive work with law enforcement, search and rescue teams, various first responders, private organizations both domestically and abroad, and the military, our team understands that when a crisis calls, seconds count. Discover why we are the leader in American-made, rapidly deployable disaster preparedness products.

Specification and design may be altered without notice due to continuous product development. LAST UPDATED DECEMBER 2023.

Proudly made in the USA.  
CAGE CODE: 7CFK2 | DUNS#: 079751064



5.0 TON HVAC SPECIFICATIONS	
DIMENSIONS (L X W X H):	60 x 47.50 x 35.50 in (152.50 x 121 x 90.50 cm)
WEIGHT:	580 lb (262.5 kg)
OPERATING RANGE, COOLING:	65 to 125°F (18 to 52°C)
OPERATING RANGE, HEATING:	-40 to 65°F (-40 to 18°C)
AIR FLOW:	2250 CFM (3820 m³/hr) @ 0.1 in wet coil
DEHUMIDIFYING:	50% RH MAX
FLEX DUCTING CONNECTION SIZE, SUPPLY:	14 in (35.50 cm) Ø
FLEX DUCTING CONNECTION SIZE, RETURN:	14 in (35.50 cm) Ø
POWER CONSUMPTION, COOLING:	8.2 kW
POWER CONSUMPTION, HEATING:	8.2 kW
POWER CONSUMPTION, WITH 9.6 KW RESISTANCE HEATER:	17.8 kW
COOLING CAPACITY:	18 kW // 62,000 BTU
HEATING CAPACITY:	17.6 kW // 60,000 BTU
HEATING CAPACITY, WITH 9.6 KW RESISTANCE HEATER:	27.5 kW // 94,100 BTU
LOCKED ROTOR AMPERAGE:	165 A
MAX RUNNING CURRENT, COOLING:	34.1 A
MAX RUNNING CURRENT, HEATING:	34.1 A
REFRIGERANT TYPE:	R410A
POWER SUPPLY:	1 PH // 208 - 230V // 60 Hz
PLUG TYPE:	50 A CS-6365
PLUG TYPE WITH RESISTANCE HEATER (10 KW):	Additional 50 A, CS-6365