



JUST THE WAY YOU LIKE IT.
CLIMATE CONTROL

1.25 TON HVAC

- **ALL-IN-ONE CLIMATE CONTROL SOLUTION.**
- **CAPABLE OF 15,000 BTU/HR COOLING AND 13,500 BTU/HR HEATING.**
- **SELF-CONTAINED AND PORTABLE.**
- **OUTDOOR, ALL-WEATHER UNIT.**

At Deployed Logix we're redefining rapid deployment. Through our extensive work with law enforcement, search and rescue teams, various first responders, private organizations both domestically and abroad, and the military, our team understands that when a crisis calls, seconds count. Discover why we are the leader in American-made, rapidly deployable disaster preparedness products.

Specification and design may be altered without notice due to continuous product development. LAST UPDATED NOVEMBER 2022.

Proudly made in the USA.
CAGE CODE: 7CFK2 | DUNS#: 079751064



| 1.25 TON HVAC SPECIFICATIONS | | | |
|------------------------------|-------------------------------------|------------------|-------------------------|
| COOLING CAPACITY: | 15,000 BTU/hr | | |
| RETURN AIR COND DB: | 20°F drop (-6.67°C) | | |
| COND AIR SUPPLY: | 550 CFM @ 0.10 in (.25 cm) wet coil | | |
| HEATING CAPACITY: | 13,500 BTU/hr heat pump | | |
| OPT RESISTANCE HEATER: | N/A | | |
| DEHUMIDIFYING: | 50% RH MAX | | |
| AMBIENT TEMPERATURE: | Min. Operating | Max. Operating | Rating |
| | 125°F (52°C) | - 40°F (- 40°C) | 95°F (35°C) |
| TEMPERATURE STAGES: | Refrigeration | | Heating |
| | 1 Stage | | 1 Stage – HP+Resistance |
| COMPRESSOR TYPE: | SCROLL | | |
| REFRIGERANT TYPE: | R410A | | |
| EVAP COIL MATERIAL: | Copper Tube / Aluminum Fin | | |
| COND COIL MATERIAL: | Copper Tube / Aluminum Fin | | |
| EXPANSION VALVE TYPE: | Bi-flow Restrictor | | |
| CIRCULATING FAN: | Forward Curve | | |
| CONDENSER FAN TYPE: | Axial | | |
| SUB BASE MATERIAL: | Galvanized Steel | | |
| CABINET FINISH: | Powder Coat | | |
| WEIGHT: | 191 lb (86.6 kg) | | |
| DIAMETER: | 10 in (25.40 cm) | | |
| DUCTS: | Supply | | Return |
| | 1 Stage | | 1 Stage – HP+Resistance |
| EXTERNAL STATIC PRESSURE: | 1 in (2.54 cm) maximum | | |
| SERVICE CONNECTIONS: | 115V AC 15A | | |
| PLUG : | (2) NEMA 5-15P | | |