



TECHNICAL DECON SHOWER // PATENT PENDING

- FREE-STANDING STALL WITH CONTAINMENT BERM, DRAIN PUMP, AND FLOOR MAT.
- INTEGRATED LAY-FLAT PLUMBING.
- COMES NEATLY PACKED IN A 75-INCH BEST CASE BY DLX™.
- HEAD-TO-TOE SPRAY COVERAGE FOR COMPLETE INDIVIDUAL DECON.

At Deployed Logix we're redefining rapid deployment. Through our extensive work with law enforcement, search and rescue teams, various first responders, private organizations both domestically and abroad, and the military, our team understands that when a crisis calls, seconds count. Discover why we are the leader in American-made, rapidly deployable disaster preparedness products.

Specification and design may be altered without notice due to continuous product development. LAST UPDATED JULY 2023.

Proudly made in the USA.
CAGE CODE: 7CFK2 | DUNS#: 079751064



TECHNICAL DECON SHOWER SPECIFICATIONS	
DEPLOYED DIMENSIONS (L X W X H):	61 x 61 x 94 in (154.94 x 154.94 x 238.76 cm)
DECON AREA:	25 ft ² (2.32 m ²)
PACKED WEIGHT:	178 lb (80.7 kg)
PACKING METHOD:	Best Case by DLX™
MIN // MAX INLET PRESSURE:	20 PSI // 80 PSI per nozzle, inline pressure limiters available by request
NOZZLE FLOW RATE:	1 GPM @ 20 PSI
PLUMBING CONSTRUCTION:	
Frame: 60 x 60 in (1.52 x 1.52 m) pop up/easy up frame	
Cover set: 10 oz PVC coated polyester, yellow	
Containment berm: 28 oz PVC coated polyester	
Drain floor: 100% Recycled HDPE	
Spray nozzles: 60° Spray angle, full cone, brass	
Plumbing: ¾ in lay-flat vinyl hose	
Fittings: Nylon	
DRAIN PUMP:	<ul style="list-style-type: none"> • 115V, 60Hz, 1.6A • 1/10 Horsepower motor • Self-priming for instant delivery or dewatering up to 6 ft (1.82 m) • 6 GPM At 1 ft (.30 m) maximum performance
KIT INCLUDES:	(1) Single piece clip-in vinyl containment surround (2) Clear observation windows with removable covers (1) Integrated lay-flat plumbing with (5) 60° full cone nozzles (1) Quick connection for optional sprayer (1) Vinyl containment berm (4) Pop-up frame 60 in (152.40 cm) (1) Rubber mat floor (1) Drain pump (1) Drain hose with strainer (1) Timer delay pump switch (1) Best Case by DLX™, 75.63 x 25 x 24 in (194.628 x 63.50 x 60.96 cm)
FEATURES // BENEFITS:	<ul style="list-style-type: none"> • 25 ft² (2.32 m²) Decon area: Allows for easy movement even when suited in bulky PPE • 8 in (20.32 cm) High, 125 gal (473.2 L) capacity containment berm (Patent Pending): Secures waste-water containment for prolonged decon events • High mounted observation ports: Helps to maintain the safety of the individual while preserving privacy • Head-to-toe full cone spray nozzles: Full deluge for complete individual decon • Tool-free set up: Simple construction for fast deployment • Double panel doors: Prevents overspray will preserving patient privacy