



STAY FRESH.
WATER LOGIX

FREESTANDING SHOWER

- TRANSLUCENT VINYL ROOF AND MESH WINDOW PROVIDE LIGHT AND VENTILATION.
- INTERIOR CURTAIN DIVIDES SHOWER AND CHANGING AREA.
- ZIPPERED ENTRY FOR COMPLETE PRIVACY.
- DESIGNED TO BE USED OUTSIDE A SHELTER IF NECESSARY.

At Deployed Logix we're redefining rapid deployment. Through our extensive work with law enforcement, search and rescue teams, various first responders, private organizations both domestically and abroad, and the military, our team understands that when a crisis calls, seconds count. Discover why we are the leader in American-made, rapidly deployable disaster preparedness products.

Specification and design may be altered without notice due to continuous product development. LAST UPDATED JUNE 2022.

Proudly made in the USA.

CAGE CODE: 7CFK2 | DUNS#: 079751064



FREESTANDING SHOWER SPECIFICATIONS	
PACKED WEIGHT:	156 lb (70.76 kg)
PACKING METHOD:	Best Case by DLX™
BERM DIMENSIONS (LWH):	66.50 x 33 x 6 in (168.91 x 83.82 x 15.24 cm)
BERM MATERIAL:	28oz Heavy-duty Vinyl
SPLASH CURTAIN DIMENSIONS (WH):	33 x 82 in (83.82 x 208.28 cm)
SPLASH CURTAIN MATERIAL:	420 Denier Pack Cloth
SHOWER CURTAIN MATERIAL:	12oz Vinyl, FR
SHOWER CURTAIN ATTACHMENT METHOD:	Hook & Loop
PLUMBING CONSTRUCTION:	USDA food grade supply hosing with Quick Connect and GHT fittings
SHOWER HEAD CONSTRUCTION:	A combination of ABS, Brass, and Stainless fittings, 1.50 GPM
SHOWER HEAD ATTACHMENT METHOD:	Screw-on frame clamp
SHOWER FRAME ATTACHMENT METHOD:	Button detent
DRAIN PUMP POWER REQUIREMENTS:	110V AC
KIT INCLUDES:	(1) Collapsible aluminum shower frame (1) Single-stall curtain with translucent roof cover (1) Quick connect shower head with frame clamp (1) Containment berm (1) Drain hose, 50 ft (12.24 m) with strainer (1) Drain pump (1) Waterproof drain pump control switch (1) Drain pump check valve (1) Raised rubber floor mat (1) Splash curtain (1) Shower caddy (1) Best Case by DLX™ Blue, 50 x 25 x 25 in (127.33 x 63.50 x 63.50 cm)