



# X-SERIES SINGLE STALL SHOWER

- **TRANSLUCENT VINYL ROOF PROVIDES LIGHT AND VENTILATION.**
- **HASSLE FREE DRAINAGE WITH PROVIDED PUMP AND DRAIN PUMP SWITCH.**
- **SHOWER CADDY BAG INCLUDED.**
- **DESIGNED FOR USE IN AN X-SERIES SHELTER.**

At Deployed Logix we're redefining rapid deployment. Through our extensive work with law enforcement, search and rescue teams, various first responders, private organizations both domestically and abroad, and the military, our team understands that when a crisis calls, seconds count. Discover why we are the leader in American-made, rapidly deployable disaster preparedness products.

Specification and design may be altered without notice due to continuous product development. LAST UPDATED JANUARY 2024.

Proudly made in the USA.  
CAGE CODE: 7CFK2 | DUNS#: 079751064



X-SERIES SINGLE STALL SHOWER SPECIFICATIONS	
PACKED DIMENSIONS (L X W X H):	38 x 25 x 24 in (96.50 x 63.50 x 61 cm)
PACKING METHOD:	Best Case by DLX™
DEPLOYED DIMENSIONS (L X W X H):	40 x 36 x 84 in (101.60 x 91.40 x 213.40 cm)
SYSTEM WEIGHT:	115 lb (52.20 kg)
POWER REQUIREMENT:	110V 60 Hz
POWER PLUG:	NEMA 5-15P
SHOWER FLOW RATE:	2.50 GPM (9.50 LPM)
DRAIN PUMP CAPACITY:	6 GPM (22.70 LPM) @ 1 ft
MIN/MAX INLET PRESSURE:	20 - 80 psi (137.90 - 551 kPa)
ENCLOSURE MATERIAL:	12 oz PVC coated vinyl
PRIVACY CURTAIN MATERIAL:	420D packcloth
CONTAINMENT BERM MATERIAL:	28 oz PVC coated vinyl
FABRIC FIRE RATING:	NFPA 701 & CPAI-84
KIT INCLUDES:	<ul style="list-style-type: none"> <li>(1) Aluminum stall frame</li> <li>(1) Shower head assembly</li> <li>(1) Drain pump w/ check valve strainer</li> <li>(1) Splashproof drain pump switch</li> <li>(1) Single Stall Shower enclosure</li> <li>(1) Shower curtain and rod</li> <li>(1) Containment berm</li> <li>(1) Toiletries caddy</li> <li>(1) Drain hose, black, 50 ft (12.24 m)</li> <li>(1) Rubber floor mat 36 x 36 in (91.44 x 91.44 cm)</li> <li>(1) Best Case by DLX™, Blue 38 x 25 x 24 in (96.50 x 63.50 x 61 cm)</li> </ul>

