

## XW-70 HEATER, 220V

PROVIDES CLEAN, HOT AIR FOR ONE OR MULTIPLE SHELTERS.

THREE DIESEL FILTERS: PUMP FILTER, SUCTION FILTER, AND INLET FILTER.

CONVENIENTLY PACKED IN A SINGLE HARD CASE.

Logix we're EASY MAINTENANCE WITH EXTERNAL PUMP AND DIAGNOSTIC LED LIGHTS. redefining rapid deployment. Through our extensive work with law enforcement, search and rescue teams, various first responders, private organizations both domestically and abroad, and the military, our team understands that when a crisis calls, seconds count. Discover why we are the leader in American-made, rapidly deployable disaster preparedness products.

At Deployed

Specification and design may be altered without notice due to continuous product development. LAST UPDATED NOVEMBER 2022.

> Proudly made in the USA. CAGE CODE: 7CFK2 | DUNS#: 079751064



XW-70 HEATER, 220V SPECIFICATIONS	
HEATING CAPACITY:	160,400 BTU/hr 47 kW
RATED AIRFLOW:	1,800 m³/hr
FUEL TYPES:	Diesel
DEPOSIT CAPACITY:	17.17 gal. (65 L)
DIESEL AUTONOMY:	14 hr
FUEL CONSUMPTION:	1.03 gal./hr (3.9 L/hr)
POWER SUPPLY:	220-240V // 50 Hz
RATED CURRENTS:	3.5 A
ABSORBED POWER:	0.8 kW
PROTECTION:	IP41
CHIMNEY PIPE DIAMETER:	5.90 in (15 cm)
OUTLET DIAMETER:	13.39 in (34 cm)
PACKED DIMENSIONS (L X W X H):	75.63 x 25 x 24 in (192.10 x 63.50 x 60.96 cm)
PACKING METHOD:	(1) Best Case By DLX™
WEIGHT:	185.2 lb (84 kg)
FEATURES:	<ul> <li>Stainless steel burn chamber</li> <li>Built-in protection from overheating</li> <li>Electronic flame control</li> <li>Powder-coated cabinet</li> <li>Optional thermostat</li> <li>Transparent fuel suction filter</li> <li>Level indicator on the fuel tank</li> <li>Trolly with wheels included</li> </ul>