



BREATHE EASY.
ISO + AIR
FILTRATION

PREDATOR 750

- 200-750 CFM, VARIABLE SPEED AIRFLOW.
- PORTABLE AND INCREDIBLY LIGHTWEIGHT (35 LB WITH FILTERS).
- DURABLE, POLYETHYLENE CABINET MADE FROM UL94HB FLAME-RETARDANT RESIN.
- USER-FRIENDLY CONTROLS AND SECURE STACKING.

At Deployed Logix we're redefining rapid deployment. Through our extensive work with law enforcement, search and rescue teams, various first responders, private organizations both domestically and abroad, and the military, our team understands that when a crisis calls, seconds count. Discover why we are the leader in American-made, rapidly deployable disaster preparedness products.

Specification and design may be altered without notice due to continuous product development. LAST UPDATED MAY 2023.

Proudly made in the USA.

CAGE CODE: 7CFK2 I DUNS#: 079751064



PREDATOR 750 SPECIFICATIONS	
DIMENSIONS (L X W X H):	25.5 x 19.5 x 20.5 in (64.77 x 49.53 x 52.07 cm)
NET WEIGHT:	35 lb (15.9 kg)
PACKED WEIGHT:	43 lb (19.5 kg)
AIR CHANGES PER HOUR:	Max 7,500 ft ³ @ 6 ACH
AIRFLOW:	200-750 CFM
POWER SUPPLY REQUIREMENTS:	110-120 VAC, 60 Hz, 15 A
CIRCUIT BREAKER:	12 A
ELECTRICAL SAFETY:	NRTL-certified to comply with UL Std. 507 & CAN/CSA Std. #C22.2 No. 113-M1984 for electrical safety
CABINET MATERIAL:	Flame-retardant resin with EPA-Registered microbial inhibitor
PREFILTER ACCESS:	Hinged access door (no tools)
FIRST STAGE PREFILTER:	1 in (2.54 cm) deep coarse particulate
SECOND STAGE PREFILTER:	2 in (5.08 cm) deep pleated particulate
OPTIONAL SECOND STAGE:	2 in (5.08 cm) deep high capacity carbon
FINAL STAGE HEPA FILTER:	Mini-pleat style filter with continuous seamless gasket, tested and certified to a minimum efficiency of 99.97% against 0.3 micron size particles
TRANSPORTABILITY:	Heavy duty, flip-up style transport handle with perfect weight balance
AMPERAGE:	1.9 A or less (daisy-chain five units on one 15 A circuit)
OPTIONAL SECOND STAGE FILTER:	2 in (5.08 cm) deep high capacity VAPOR-LOCK carbon filter for odors
MOTORIZED IMPELLER:	Rated for 100,000 hours with thermal overload protection, auto reset, 60 Hz, single-phase
RUBBER FEET:	Yes

