



VINYL FLOOR

- **MILDEW RESISTANT.**
- **FORMS A 6-INCH SANITARY BERM FOR THE ASAP® AND A 8-INCH FOR THE X-SERIES.**
- **FLAME RESISTANT.**
- **ONE CONTINUOUS WEAR-RESISTANT PIECE.**

At Deployed Logix we're redefining rapid deployment. Through our extensive work with law enforcement, search and rescue teams, various first responders, private organizations both domestically and abroad, and the military, our team understands that when a crisis calls, seconds count. Discover why we are the leader in American-made, rapidly deployable disaster preparedness products.

Specification and design may be altered without notice due to continuous product development. LAST UPDATED MARCH 2023.

Proudly made in the USA.
CAGE CODE: 7CFK2 | DUNS#: 079751064



VINYL FLOOR SPECIFICATIONS	
TOTAL WEIGHT:	15 oz / yd ² (508 g / m ²)
ADHESION:	Dielectric Weld, (RF) 12 lb / 2 in (53 N / 2.5 cm)
GRAB TENSILE:	350 x 315 lb (1,556 x 1,401 N)
STRIP TENSILE:	256 x 245 lb (1,139 x 1,089 N)
TONGUE TEAR:	60 x 45 lb (267 X 200 N)
ELMENDORF TEAR:	14.1+ x 14.1+ lb (62.7+ X 62.7+ N)
LOW TEMPERATURE:	@ -65° F (@ -53.89° C)
MILDEW RESISTANCE:	No growth
OPACITY:	Transmission of visable light Fed-St-191A, Method 5781 0.020 Foot-Lamberts of light transmission max.
FLAME RESISTANCE:	After flame - 2 sec. max, char lenght - less than 50% consupion
HYDROSTATIC RESISTANCE:	
ASTM D 751: Procedure B, procedure 1 (126 + cm)	
ASTM D 751: Procedure A, procedure 1 (400 psi, 2,758 kPa)	
FEATURES:	<ul style="list-style-type: none"> MIL-PRF-44271C, MIL-PRF-44103D, USIFI-PRF-44103A Class 3 or 4, Grade B Vinyl, laminated, polyester