



PICTURED WITHOUT SHELTER COVER
FOR GREATER CLARITY

RINSE THE RISK AWAY
DECON

ASAP® TWO-LANE DECON SHOWER

- **TOOL-FREE SETUP FOR FAST AND EASY DEPLOYMENT.**
- **INTEGRATED LAY-FLAT PLUMBING.**
- **QUICK-CONNECTING OVERHEAD AND HAND-HELD SPRAYERS.**
- **ACCOMMODATES AMBULATORY AND NON-AMBULATORY SERVICE.**

At Deployed Logix we're redefining rapid deployment. Through our extensive work with law enforcement, search and rescue teams, various first responders, private organizations both domestically and abroad, and the military, our team understands that when a crisis calls, seconds count. Discover why we are the leader in American-made, rapidly deployable disaster preparedness products.

Specification and design may be altered without notice due to continuous product development. LAST UPDATED JULY 2023.

Proudly made in the USA.
CAGE CODE: 7CFK2 | DUNS#: 079751064



ASAP® TWO-LANE DECON SHOWER SPECIFICATIONS

DEPLOYED DIMENSIONS (L X W X H):	18 x 16 x 8 ft (5.48 x 4.87 x 2.43 m)
DISROBE AREA (2) (L X W):	66 x 56 in (167.64 x 142.24 cm)
RINSE AREA (2) (L X W):	80 x 56 in (203.20 x 142.24 cm)
REDRESS AREA (2) (L X W):	66 x 56 in (167.64 x 142.24 cm)
MIN // MAX INLET PRESSURE:	20 PSI - 80 PSI max
DELUGE NOZZLE (5) FLOW RATE:	5 GPM @ 20 PSI (18.9 LPM @ 137.9 kpa)
HAND SPRAY NOZZLES (4) FLOW RATE:	4 GPM @ 20 PSI (15.1 LPM @ 137.9 kpa)
TOTAL SYSTEM MAX FLOW RATES:	9 GPM @ 20 PSI (34 LPM @ 137.9 kpa)
WATER MANIFOLD INLET:	¾ in Female GHT
DRAIN PUMP:	115V, 60Hz, 1.6 A, 6 GPM @ 1 ft, ¾ Male GHT
MATERIALS:	
Entry // exit end walls: 14 oz/yd ² (396.8 g/m ²) PVC coated polyester // Meets or exceeds MIL-PRF-44103D // USIFI-PRF-44103A	
Decon corridors: 10 oz PVC coated polyester // yellow	
Containment berm: 28 oz PVC coated polyester	
Drainage flooring: 1.50 in (3.81 cm) HDPE anti-skid recycled plastic	
Spray nozzles (9): 60° Full cone // brass	
Plumbing: ¾ in lay-flat vinyl hose // ¾ in nylon reinforced vinyl hose	
Fittings: Nylon // brass // polypropylene // polyethylene // stainless steel	
KIT INCLUDES:	<ul style="list-style-type: none"> (1) 2-Lane Decon corridor with integrated plumbing with carry bag (1) Containment berm 80 x 112 in (203.20 x 284.48 cm) (2) Double door entry/exit endwall (1) Supply manifold with carry bag (4) Coiled quick connect hose with hand-held sprayer (1) Carry bag for sprayers and hoses (4) Plastic S-hook carabiner (8) Rigid drain floor sections 53 x 17.75 in (134.62 x 45.08 cm) (2) Rigid drain floor section 53 x 5.50 in (134.62 x 13.97 cm) (2) Drain strainer with hose (2) Waste water drain pump (2) Drain pump switch (1) Spare parts kit
FEATURES // BENEFITS:	<ul style="list-style-type: none"> • Unassisted or assisted decon deluge corridor capability: Allows walkthrough decon for hands free rinse off using multiple spray nozzles or hand operated sprayers • Simple water supply controls: Allows for easy use and low training threshold • Coiled hand-held sprayers with full cone nozzles: Prevents sprayers from becoming tangled in the unit and allows for a full deluge of water on a patient • Tool-free setup and strike: No special skills required to deploy • Side opening doorways: Prevents overspray while preserving patient privacy • Large containment berm holds up to 314 US Gal (11890 L): Extends decon operations and allows for superior containment of waste water • Quick connect manifold: Water manifold has pre-installed quick connects for fast setup and take down • Ambulatory or non-ambulatory capability: The decon deluge section is long enough to accommodate standard backboards or gurneys for non-ambulatory decon service • Dual drop chutes on endwalls: Allows for safe disposal of contaminated articles and passage of clean items post decon • Raised anti-skid rigid flooring made from recycled HDPE plastic: Prevents excessive contamination from run-off while also providing more secure footing in wet environment