



JUST THE WAY YOU LIKE IT.
CLIMATE CONTROL

3-SPEED OVERHEAD FAN

- **SIMPLE TO INSTALL, NO TOOLS REQUIRED.**
- **3-SPEED MOUNTABLE CONTROL.**
- **LIGHTWEIGHT, EASY TO STORE AND TRANSPORT.**
- **MODULAR SWIVELING BRACKET INSTALLS IN A VARIETY OF LOCATIONS.**

At Deployed Logix we're redefining rapid deployment. Through our extensive work with law enforcement, search and rescue teams, various first responders, private organizations both domestically and abroad, and the military, our team understands that when a crisis calls, seconds count. Discover why we are the leader in American-made, rapidly deployable disaster preparedness products.

Specification and design may be altered without notice due to continuous product development.
LAST UPDATED NOVEMBER 2023.

Proudly made in the USA.
CAGE CODE: 7CFK2 | DUNS#: 079751064



3-SPEED OVERHEAD FAN SPECIFICATIONS	
FAN DIMENSIONS (L X W X H):	26 x 23.50 x 7.50 in (66.04 x 59.69 x 19.05 cm)
WEIGHT:	16 lb (7.2 kg)
POWER:	1PH // 110V // 60Hz // plug NEMA 5-15P
POWER CONSUMPTION:	145W // 1.3A
PRODUCT SOS NUMBER:	#CCXOHF3
AIRFLOW:	
High: 3000 CFM	
Mid: 2400 CFM	
Low: 1700 CFM	
INSTALL LOCATION:	Fits bar or cable style arch headers
MOTOR CERTIFICATIONS:	ETL listed
MATERIALS:	
Frame Bracket: Aluminum // powder coated	
Carry Bag: 18 oz/yd ² (610.30 g/m ²) PVC coated polyester // black // fire-retardant	
KIT INCLUDES:	(1) Fan assembly with mounting bracket and fan controller (1) Carry bag
FEATURES // BENEFITS:	<ul style="list-style-type: none"> • Plug and play: Easy, tool-free installation for fast deployment: just hang, plug in, and turn on. • Modular swiveling hanging bracket: Bracket mounts to wide variety of locations inside the shelter and allows directional adjustment of the fan. • Multi-speed controller: Controls the fan speed based on your needs and climate conditions. Add additional units to generate optimum low power air circulation.