



JUST THE WAY YOU LIKE IT.
CLIMATE CONTROL

INSULATION LINER

- **IMPROVES CLIMATE CONTROL BY 5 TO 10 DEGREES FAHRENHEIT.**
- **COMPLETE WITH SCREEN WINDOWS & INTERIOR CONNECTION POINTS FOR ACCESSORIES.**
- **DOUBLES AS A SOUND BARRIER TO IMPROVE NOISE CONTROL.**
- **CUSTOMIZABLE FOR ANY PORTABLE SHELTER.**

At Deployed Logix we're redefining rapid deployment. Through our extensive work with law enforcement, search and rescue teams, various first responders, private organizations both domestically and abroad, and the military, our team understands that when a crisis calls, seconds count. Discover why we are the leader in American-made, rapidly deployable disaster preparedness products.

Specification and design may be altered without notice due to continuous product development. LAST UPDATED JULY 2022.

Proudly made in the USA.
CAGE CODE: 7CFK2 | DUNS#: 079751064



INSULATION LINER SPECIFICATIONS		
WEIGHT:	Method C, 6.25 oz/yd ² +/- 5%	ASTM D 3776
THICKNESS:	-96 .01 in (-243.86 cm) maximum	ASTM D 1777-96
THERMAL RESISTANCE:	2.2, overall R-Value	ASTM C 1363
TEAR STRENGTH:	5.5/5.5 lb minimum	ASTM D 1424
	17.0/17.0 lb minimum	ASTM D 2261
ABRASION RESISTANCE:	AATCC Gray Scale 2.5 minimum	ASTM D3886 1,000 cycles
WATER PERMEABILITY:		
Initial: No leakage/Pass		
After Cold Crack ASTM D751 @ -40°F: No leakage/Pass		
BLOCKING:	1.0 maximum, 180F exposure 30 minutes	ASTM D 751
RESISTANCE TO COLD CRACK -40° F:	PASS	FEDERAL STANDARD 191 TEST METHOD 5874
MILDEW RESISTANT:	PASS	AATCC 30
OTHER:	Meets or exceeds all specifications of ASTM D 6413, CPAI 84, NFPA 701 & CSFM	