



LED STRING LIGHTS

- **WATER-RESISTANT.**

- **REDUCES WEIGHT, VOLUME, ENERGY CONSUMPTION, AND HEAT OUTPUT.**

- **MORE AFFORDABLE THAN ITS LIGHTING COUNTERPARTS.**

- **EASY SETUP AND TAKEDOWN.**

At Deployed Logix we're redefining rapid deployment. Through our extensive work with law enforcement, search and rescue teams, various first responders, private organizations both domestically and abroad, and the military, our team understands that when a crisis calls, seconds count. Discover why we are the leader in American-made, rapidly deployable disaster preparedness products.

Specification and design may be altered without notice due to continuous product development. LAST UPDATED JUNE 2022.

Proudly made in the USA.
CAGE CODE: 7CFK2 I DUNS#: 079751064



LED STRING LIGHTS SPECIFICATIONS								
MODEL:	ASAP-12	ASAP-18	ASAP-HUB	X-16	X-24	X-32	X-40	X-HUB
LENGTH:	18 ft (5.49 m)	24 ft (7.32 m)	27 ft (8.23 m)	24 ft (7.32 m)	32 ft (9.75 m)	40 ft (12.19 m)	48 ft (14.63 m)	44 ft (13.41 m)
PLUG END LENGTH:	8 ft (2.44 m)							
WEIGHT:	4 lb (1.8 kg)	5 lb (2.3 kg)	4 lb (1.8 kg)	5 lb (2.3 kg)	10 lb (4.5 kg)	13 lb (5.9 kg)	14 lb (6.4 kg)	8 lb (3.6 kg)
BULB QUANTITY:	5	7	8	6	10	14	18	8
VOLTAGE:	85-265V AC							
STANDARD PLUG TYPE:	US Type A							
OPTIONAL PLUG TYPE:	EU/UK Type C, E, F, G							
BULB TYPE:	5w LED, 450 lm, 3000 k, E26 Base							
RATING:	CE Rated, ETL Rated, and IP65 Rating for Bulb, Housing, Connector							
ATTACHMENT METHOD:	Rubber Coated Wire Gear Ties							
PACKING METHOD:	DLX Labeled Tote Bag 14 x 17 in (35.56 x 43.18 cm)			DLX Labeled Duffel Bag, Small				
FEATURES:	<ul style="list-style-type: none"> • Linkable strands; Easy to add more or extend into connected shelters. • IP65 Rated. Can be used anywhere. • Bright, efficient LED bulbs. Long-lasting with lower power consumption. • No glass. Safer to use without parts breaking and causing hazards. • Easy connections systems can be mounted anywhere you need lighting. 							

