

UV WATER FILTRATION UNIT

PURIFIED WATER OUTPUT: 200 GAL./HR (757.1 L/HR).

At Deployed

Logix we're

redefining rapid

deployment. Through

our extensive work with law

enforcement, search and rescue

teams, various first responders, private

organizations both domestically and abroad,

and the military, our team understands that when

a crisis calls, seconds count. Discover why we are

the leader in American-made, rapidly deployable disaster

preparedness products.

Specification and design may be altered without notice due to continuous product development. LAST UPDATED NOVEMBER 2023.

Proudly made in the USA.

CAGE CODE: 7CFK2 | DUNS#: 079751064

THREE-STAGE FILTRATION WITH UV LIGHT DISINFECTION.

- ALL STAINLESS INTERIOR CONSTRUCTION FOR EASE OF CLEANING AND SANITATION.
 - GFCI PROTECTED ELECTRICAL SYSTEM.



WATER FILTRATION UNIT SPECIFICATIONS			
DIMENSIONS (L X W X H):	38 x 25 x 24 in (96.52 x 63.50 x 60.96 cm)		
SYSTEM WEIGHT:	118 lb (53.40 kg)		
OPERATING RANGE:	40 to 120° F (4 to 49° C)		
SETUP TIME:	20 min		
SETUP PERSONNEL:	1		
FILTERS:	Stage 1 Particulate 50 mesh	Stage 2 Sediment	Stage 3 Fine partical ceramic
UV LAMP DOSE AT 4 GPM (15.1 LPM):	50 Mesh	25-1 µm 80 mJ/cm ²	0.2 μm
WATER OUTPUT:	200 gal./hr (757.1 L/hr)		
POWER REQUIREMENT:	110V // 60 Hz		
POWER COMSUMPTION (NORMAL OPERATION):	1265 W		
WATER COMPONENT:	NFS Compliant		
ELECTRICAL COMPONENTS:	UL Listed		
COMPONENT LIFE CYCLE (VARIES ON WATER QUALITY)*			
UV SANITIZER LAMP:	Approximately 9,000 hrs*		
STAGE 1 FILTER - PARTICULATE:	Washable		
STAGE 2 FILTER - SEDIMENT:	20,000 - 30,000 gal. (75 708.3 - 113 562.4 L)*		
STAGE 3 FILTER - FINE PARTICLE CERAMIC:	PAC 2.5-10 Filter chlorine capacity 5,000 gal. (18 927.1 L)		
KIT INCLUDES:	 (1) Three-stage water filtration system with UV water disinfection lamp (2) UV Replacement bulb (1) Replacement quartz tube (2) Polypropylene 1 micron sediment filter (2) Argonide NanoCeram 0.2 micron filter (1) 50 Micron mesh particulate filter (1) Hose bag (1) Blue hose, clean output, 25 ft (7.62 m) (1) Black hose, dirty intake, 25 ft (7.62 m) (1) Filter wrench (1) OEM UV manual (4) Knobs for manifold attachment (1) Spare parts kit (1) USB LED light (1) Best Case by DLX™, blue 38 x 25 x 24 in (96.52 x 63.5 x 60.96 cm) 		